

CANBUILT MFG.

Toll-Free in Canada: 1-888-607-2926 Phone: 416-749-6555 Fax: 416-749-7597 Email: sales@canbuilt.com Website: www.canbuilt.com 103 Milvan Drive, Toronto, Ontario, Canada, M9L 1Z7

DIESEL EXHAUST FLUID (DEF) PUMP

Model # DEF-500 115v DEF Pump System

FEATURES:

- Standard 115v operation
- · Sealed solution bung adapter with buttress thread
- 8 feet Goodyear DEF dispensing hose with stainless steel clamps
- Stainless steel automatic shutoff nozzle
- Standard 2" bung adapter
- For 205 litre drums
- Pump length 40 inches
- Fluid output of 5 gpm



DEF PUMPS & CRYSTALIZATION

DEF WILL CREEP:

This simply means that DEF will find its way through every possible opening Once DEF is exposed to air, the water will evaporate leaving behind a crystallized white powderyresidue This residue can be cleaned with do-ionized water and a bit a scrubbing As you can imagine, allowing the DEF to crystallize in a pump is not a good idea. It can lead to premature pump failure

BEST PRACTICES TO FOLLOW FOR DEF PUMPS:

Don't allow the barrel, tote or tank to run dry. This introduces air into the pump and will cause crystallization

If at all possible, the pump should be used regularly to keep crystallization from occurring

If the pump will not be used for an extended period of time, it should be flushed with do-ionized water to prevent crystallization If crystallization has occurred in your pump, DO NOT try to pump it out. Open the pump and clean it with de-ionized water Following these practices will ensure that you DEF pump will last and perform as intended.

QUALITY · PERFORMANCE · LONGEVITY