



CANBUILT MFG.

www.canbuilt.com

February 2025

FILTER LUBRICATOR REGULATORS



**Model#
FLR-1559**



**Model#
FLR-1560**



**Model#
FLR-014**



**Model#
FLR-238
FLR-212**



Model# DC-1100



Model# DC-1101



Model# DC-1102

Model #	FLR-1559	FLR-1560	FLR-014	FLR-238	FLR-212	DC-1100	DC-1101	DC-1102
Joint Pipe Bore	1/4"	1/4"	1/4"	3/8"	1/2"	1/4"	3/8"	1/2"
Medium	Air							
Filtering Element Roughness	40 Microns							
Operating Pressure range	Drain Type: 25 PSI - 115 PSI							
Max. Adjustable Pressure	115 PSI	150 PSI				250 PSI		
Operating Temperature Range	5-60°C					4.4° to 65.55° C		
Cup Filter Capacity	0.507oz	0.507oz	0.507oz	2.028oz	2.028oz	0.507oz	0.507oz	2.028oz
Oil Feed Cup Capacity	0.845oz	0.845oz	0.845oz	3.043oz	3.043oz	0.845oz	0.845oz	3.043oz
Suggested Lube	ISO VG32 or Same Grade Oil					ISO VG32 or Same Grade Oil		
Constituents	Filter	YES	YES	YES	YES	YES	YES	YES
	Lubricator	NO						
	Regulator	YES	YES					

Model# C-F15931A

Pre-Filter 1/2" for C-20U,C30,C50 air Dryers and Blast Cabinets. If a blast cabinets is operated without an air dryer, it may compromise warranty.

Specifications:

- Port Size: 1/2 inch NPT
- Flow Rate: 122.5 SCFM (approximately 3,470 L/min)
- Filter Rating: 5 microns

- Pressure Rating: 28 to 140 psi (1.9 to 9.6 bar)
- Temperature Range: 41°F to 120°F (5°C to 49°C)
- Bowl Capacity: 2.19 oz
- Bowl Material: Polycarbonate with guard
- Drain Type: Internal auto drain
- Filter Materials: Acetal, aluminum, bronze, nitrile, polycarbonate, stainless steel, and steel
- Overall Width: 2.756 inches
- Mounting: Modular mounting compatible



103 Milvan Drive, Toronto, Ontario, Canada, M9L 1Z7

Toll-Free in Canada: 1-888-607-2926 Phone: 416-749-6555 Fax: 416-749-7597 Email: sales@canbuilt.com