



# CANBUILT MFG.

www.canbuilt.com

February 2023

## FILTER LUBRICATOR REGULATORS



**Model# DC-1100**



**Model# DC-1101**



**Model# DC-1102**



**Model#  
FLR-1559**



**Model#  
FLR-1560**



**Model#  
FLR-014**



**Model#  
FLR-238  
FLR-212**



**Model#  
FLR-312**

Model #	FLR-1559	FLR-1560	FLR-014	FLR-238	FLR-212	FLR-312	DC-1100	DC-1101	DC-1102
Joint Pipe Bore	1/4"	1/4"	1/4"	3/8"	1/2"	1/2"	1/4"	3/8"	1/2"
Medium	Air								
Filtering Element Roughness	40 Microns								
Operating Pressure range	Drain Type: 25 PSI - 115 PSI								
Max. Adjustable Pressure	115 PSI	150 PSI				135 PSI	250 PSI		
Operating Temperature Range	5-60°C						4.4° to 65.55° C		
Cup Filter Capacity	0.507oz	0.507oz	0.507oz	2.028oz	2.028oz		0.507oz	0.507oz	2.028oz
Oil Feed Cup Capacity	0.845oz	0.845oz	0.845oz	3.043oz	3.043oz		0.845oz	0.845oz	3.043oz
Suggested Lube	ISO VG32 or Same Grade Oil						ISO VG32 or Same Grade Oil		
Costituents	Filter	YES	YES				YES		
	Lubricator	NO		YES	YES	YES	NO	YES	YES
	Regulator	YES	YES				YES		

103 Milvan Drive, Toronto, Ontario, Canada, M9L 1Z7

Toll-Free in Canada: 1-888-607-2926 Phone: 416-749-6555 Fax: 416-749-7597 Email: sales@canbuilt.com