



CANBUILT MFG.

www.canbuilt.com

December 2022

AIR OPERATED DOUBLE DIAPHRAGM PUMPS

These pumps are well suited for industrial or automotive applications. They feature an air distribution fully serviceable externally, through a fully bolted construction.



MODEL # DP-3600



MODEL # DP-4001

SPECIFICATIONS	MODEL DP-3600	MODEL DP-4001
Inlet/Outlet	3/4"	1"
Air inlet	1/4"	1/4"
Flow Rate	16 GPM/60 LPM	24 GPM/90 LPM
Max Air Inlet Pressure	115 PSI / 8Bar	115PSI / 8BAR
Max Outlet Pressure	115 PSI / 8Bar	115 PSI / 8Bar
Max Diameter Solid	1/8"	1/8"
Body Construction	Polypropylene	Aluminum
Membrane	Nitrile, Fluorin Rubber	
Fluid Compatibility	Oils, Diesel, Kerosene	

**REQUIRED:
Filter / Regulator
Model # FLR-1559**

1/4" Air line filter with water drain, regulator, gauge and ball valve .40 micron filter- 1/4" NPT Inlet / Outlet. Regulate air flow for optimum pump efficiency. On/Off valve allows user to turn on or turn off the diaphragm pump.



**3/4" Brass Y Strainer
Model # DP-3501YB**

Strains the fluid from larger debris/particulates to protect the pump



**3/4" Stainless Y Strainer
Model # DP-3500Y**



103 Milvan Drive, Toronto, Ontario, Canada, M9L 1Z7

Toll-Free in Canada: 1-888-607-2926 Phone: 416-749-6555 Fax: 416-749-7597 Email: sales@canbuilt.com