



CANBUILT MFG.

www.canbuilt.com

November 2021

FILTER LUBRICATOR REGULATORS



Model# DC-1100



Model# DC-1101



Model# DC-1102



**Model#
FLR-1559**



**Model#
FLR-1560**



**Model#
FLR-014**



**Model#
FLR-238
FLR-212**



**Model#
FLR-312**

Model #	FLR-1559	FLR-014	FLR-238	FLR-212	FLR-312	DC-1100	DC-1101	DC-1102
Joint Pipe Bore	1/4"	1/4"	3/8"	1/2"	1/2"	1/2"	1/4"	3/8"
Medium	Air							
Filtering Element Roughness	40 Microns							
Operating Pressure range	Drain Type: 25 PSI - 115 PSI							
Max. Adjustable Pressure	115 PSI				135 PSI	250 PSI		
Operating Temperature Range	5-60°C					4.4° to 65.55° C		
Cup Filter Capacity	0.507oz	0.507oz	2.028oz	2.028oz		0.507oz	0.507oz	2.028oz
Oil Feed Cup Capacity	0.845oz	0.845oz	3.043oz	3.043oz		0.845oz	0.845oz	3.043oz
Suggested Lube	ISO VG32 or Same Grade Oil					ISO VG32 or Same Grade Oil		
Weight	0.7 Kg	0.5 Kg	0.7 Kg	0.7 Kg		0.7 Kg	0.5 Kg	0.7 Kg
Costituents	Filter	YES				YES		
	Lubricator	NO	YES	YES	YES	NO	YES	YES
	Regulator	YES				YES		

103 Milvan Drive, Toronto, Ontario, Canada, M9L 1Z7

Toll-Free in Canada: 1-888-607-2926 Phone: 416-749-6555 Fax: 416-749-7597 Email: sales@canbuilt.com