



# CANBUILT MFG.

www.canbuilt.com

March 2026

## FILTER LUBRICATOR REGULATORS



**Model#  
FLR-1559**



**Model#  
FLR-1560**



**Model#  
FLR-014**



**Model#  
FLR-238  
FLR-212**



**Model# DC-1100**



**Model# DC-1101**



**Model# DC-1102**

Model #	FLR-1559	FLR-1560	FLR-014	FLR-238	FLR-212	DC-1100	DC-1101	DC-1102	
Joint Pipe Bore	1/4"	1/4"	1/4"	3/8"	1/2"	1/4"	3/8"	1/2"	
Medium	Air								
Filtering Element Roughness	40 Microns								
Operating Pressure range	Drain Type: 25 PSI - 115 PSI								
Max. Adjustable Pressure	115 PSI	150 PSI				250 PSI			
Operating Temperature Range	5-60°C					4.4° to 65.55° C			
Cup Filter Capacity	0.507oz	0.507oz	0.507oz	2.028oz	2.028oz	0.507oz	0.507oz	2.028oz	
Oil Feed Cup Capacity	0.845oz	0.845oz	0.845oz	3.043oz	3.043oz	0.845oz	0.845oz	3.043oz	
Suggested Lube	ISO VG32 or Same Grade Oil					ISO VG32 or Same Grade Oil			
Constituents	Filter	YES	YES	YES	YES	YES	YES	YES	YES
	Lubricator	NO					NO		
	Regulator	YES	YES				YES		

### Model# C-F15931A

Pre-Filter 1/2" for C-20U,C30,C50 air Dryers and Blast Cabinets. If a blast cabinets is operated without an air dryer, it may compromise warranty.

#### Specifications:

- Port Size: 1/2 inch NPT
- Flow Rate: 122.5 SCFM (approximately 3,470 L/min)
- Filter Rating: 5 microns

- Pressure Rating: 28 to 140 psi (1.9 to 9.6 bar)
- Temperature Range: 41°F to 120°F (5°C to 49°C)
- Bowl Capacity: 2.19 oz
- Bowl Material: Polycarbonate with guard
- Drain Type: Internal auto drain
- Filter Materials: Acetal, aluminum, bronze, nitrile, polycarbonate, stainless steel, and steel
- Overall Width: 2.756 inches
- Mounting: Modular mounting compatible



103 Milvan Drive, Toronto, Ontario, Canada, M9L 1Z7

Toll-Free in Canada: 1-888-607-2926 Phone: 416-749-6555 Fax: 416-749-7597 Email: sales@canbuilt.com