



CANBUILT MFG.

www.canbuilt.com

November 2021

FILTER LUBRICATOR REGULATORS



Model# DC-1100



Model# DC-1101



Model# DC-1102



**Model#
FLR-1559**



**Model#
FLR-1560**



**Model#
FLR-014**



**Model#
FLR-238
FLR-212**



**Model#
FLR-312**

Model #	FLR-1559	FLR-014	FLR-238	FLR-212	FLR-312	DC-1100	DC-1101	DC-1102	
Joint Pipe Bore	1/4"	1/4"	3/8"	1/2"	1/2"	1/2"	1/4"	3/8"	
Medium	Air								
Filtering Element Roughness	40 Microns								
Operating Pressure range	Drain Type: 25 PSI - 115 PSI								
Max. Adjustable Pressure	115 PSI				135 PSI	250 PSI			
Operating Temperature Range	5-60°C					4.4° to 65.55° C			
Cup Filter Capacity	0.507oz	0.507oz	2.028oz	2.028oz		0.507oz	0.507oz	2.028oz	
Oil Feed Cup Capacity	0.845oz	0.845oz	3.043oz	3.043oz		0.845oz	0.845oz	3.043oz	
Suggested Lube	ISO VG32 or Same Grade Oil					ISO VG32 or Same Grade Oil			
Weight	0.7 Kg	0.5 Kg	0.7 Kg	0.7 Kg		0.7 Kg	0.5 Kg	0.7 Kg	
Costituents	Filter	YES	YES	YES	YES	YES	YES	YES	YES
	Lubricator	NO					NO		
	Regulator	YES					YES		

103 Milvan Drive, Toronto, Ontario, Canada, M9L 1Z7

Toll-Free in Canada: 1-888-607-2926 Phone: 416-749-6555 Fax: 416-749-7597 Email: sales@canbuilt.com