



CANBUILT MFG.

Toll-Free in Canada: 1-888-607-2926 Phone: 416-749-6555 Fax: 416-749-7597
Email: sales@canbuilt.com Website: www.canbuilt.com

103 Milvan Drive,
Toronto, Ontario,
Canada, M9L 1Z7

STANDARD DUTY 55:1 PUMP ONLY FOR PAIL

MODEL # **GP-12541**

- 55:1 pressure ratio air operated grease pump for transfer and distribution of grease through pipeworks, hose reels and guns. The pump can be mounted on mobile units or drums. Adjustable (2" BSP) bung adapter included.

TECHNICAL SPECIFICATIONS

- Max. air pressure Max.: 10 bar (142 psi)
- Min. air pressure Min.: 3 bar (42 psi)
- Max. grease pressure Max.: 550 bar (7800 psi)
- Free grease delivery: 600 g/min (21 ounce/min)
- Air inlet thread: G $\frac{1}{4}$ " f ($\frac{1}{4}$ " BSP (f)
- Grease outlet thread: G $\frac{1}{4}$ " f ($\frac{1}{4}$ " BSP (f)
- Weight: 4,85 Kg. (10 $\frac{3}{4}$ lbs)
- Length: 36-1/2"
- Pump Height: 77/8"
- Tube length: 28-1/2"



**Over 105 Years of Experience.
European Design and quality**



QUALITY • PERFORMANCE • LONGEVITY