



CANBUILT MFG.

Toll-Free in Canada: 1-888-607-2926 Phone: 416-749-6555 Fax: 416-749-7597
Email: sales@canbuilt.com Website: www.canbuilt.com

103 Milvan Drive,
Toronto, Ontario,
Canada, M9L 1Z7

STANDARD DUTY GREASE PUMP KITS

Model # **GP-12752**

60:1- Drum Grease pump w/Adapter 3/8" to 1/4"

- Air operated 60:1 ratio grease pump for 60 kg keg.
- For both mobile and fixed installations.
- Includes Bung adapter G 2"

A heavy-duty pneumatic grease pump for applications where maintaining good flows at high pressure is required.

It is a high-performance grease pump well suited for most commercial & industrial greasing applications.



Technical data	12751-12752
Pressure ratio	60:1
Max air pressure	1.0 Mpa/ 145 psi
Min air pressure	0.4 Mpa/ 58 psi
Max grease pressure	60.0 Mpa/ 8700 psi
Burst pressure	Min. 100 Mpa/ 14500 psi
Capacity, free flow, air pressure 0,7 Mpa, NLGI 2, 20°C Through 10 m 1/4"-hose and grease gun (14612)	1100 g/min, 2.42 lbs 660 g/min, 1.46 lbs
Air inlet thread	BSP 1/4" female
Grease outlet thread	BSP 3/8" female
Noice level at 0,7 MPa	84 dB
Drum adapter, G 2" (BSP 2")	Included

Pump model	12751	12752
Total length	1000 mm, 39 3/8"	1180 mm, 46 15 / 32"
Pump tube length	750 mm, 29 1/2"	930 mm, 36 5/8"
Pump tube Ø	30 mm, 17/32"	30 mm, 17/32"
Weight	5.8 kg/ 12.4 lbs	6.5 kg / 13.9 lbs

Over 105 Years of Experience.
European Design and quality

QUALITY • PERFORMANCE • LONGEVITY