



# CANBUILT MFG.

Toll-Free in Canada: 1-888-607-2926 Phone: 416-749-6555 Fax: 416-749-7597  
Email: sales@canbuilt.com Website: www.canbuilt.com

103 Milvan Drive,  
Toronto, Ontario,  
Canada, M9L 1Z7

## M&B 3 SERIES TIRE CHANGERS SWING ARM TYPE

**NEW VARIABLE SPEED  
100% FASTER THAN SINGLE SPEED  
NOW MORE POWER & CONTROL!**






### Model# **TC-328-2S** 31" Diameter Inside Clamping

**Powerful, practical & space saving**



Shown with  
Technoswing Arm  
Model #TC-0300TS

Efficient tubeless inflation through extra circuit with direct passage to the jaws outlets, allowing the beading in any type of tire



Turntable with mobile clamps (TC-328it)



**PUSH THE PEDAL TO THE METAL**

**POWER INVERTER** with double variable speed (10 to 17 RPM) with pedal control. Provides constant torque from beginning to end.  
**MORE SPEED, POWER and CONTROL**



The special shape and toughness of the bead breaking arm ensure the rapid bead breaking. Opening range plate is easily adjustable to be fitted to all types of wheels (max. width 16").

**QUALITY • PERFORMANCE • LONGEVITY**

# Technoswing Arm

## Model# **TC-0300TS**

for the TC-322it , TC-328it and TC-328-2S



If you work on hard and large sized wide and low profile tires (UHP e Run Flat (RSC)), you need this arm. The tough structure is designed with 1 air cylinder of 3 1/4" (80 mm) that is not subject to flexion during heavy work operations. Comes pre-assembled and tested when ordered with TC322it, TC328it or TC-328-2S model machines.



Positions the rim during locking operation



Allows the bead to be held in the rim during mounting



Roller arm with the option of operating under the tire greatly helps in the demounting and mounting



Maintains the tire bead on the rim facilitating the demounting procedure

# Accessories



SET OF 2 EA # **MB199130**

## **NYLON DUCKBILL PROTECTORS FOR ALUMINUM RIMS**

Universal fit, for most standard tire machines. Nylon protectors snap onto Duckbill to protect aluminum rims from accidental damage. **Sold as a kit: includes 2 Duckbill protectors and 2 Duckbill heel protectors**



Model # **MB200589**

## **WHEEL CLAMP SLIDE GUARD KIT**

Nylon protectors snap onto rimclamp sliders and remain in place to protect aluminum rims from accidental damage  
**Sold as a kit: includes 4 slider protectors**



Model # **MB201370**

## **PLASTIC MOUNTING/DEMOUNTING TOOL**



Model # **MB200215**

## **BEAD BREAKER PROTECTOR FOR ALUMINUM RIMS**

Nylon protector covers hydraulic bead breaker and remains in place to protect aluminum rims from accidental damage while breaking the bead



Model # **MB201359**

## **DEMOUNT LEVER PLASTIC PROTECTOR**

Nylon protector covers Demount lever to protect aluminum rims from accidental damage while mounting or demounting the tire



Model # **MB200242**

## **PLASTIC JAW INSERT FOR WEDGE CUP**

Nylon protectors snap onto wheel clamp wedge to protect aluminum rims from damage



Model # **MB200604**

## **MOTORCYCLE ADAPTER, SET OF 4**



Model # **MB200606**

## **SCOOTER ADAPTER, SET OF 4**

Adapters to change tires on scooters, golf carts and small diameter tires

# Specifications

SPECIFICATIONS	MODEL # TC-328iT
Net weight	206 Kg.
Operating pressure	115 - 175 PSI
Bead breaker force	2500 kg
Max wheel diameter	44" (1120 mm.)
Wheel width	3" - 15"
Rim diameter (locked internally)	12" - 31"
Rim diameter (locked externally)	10" - 28"
Motor	110v 1PH